

Vishal Pipes Limited

Series		Light						Medium					Heavy				
Normal Bore		O.D	Outside Dia.		Wall Thick .	Weight		Outside Dia.		Wall Thick .	Weight		Outside Dia.		Wall Thick .	Weight	
Inc .	M m	Mm	Min. mm	Max . mm	Mm	P/E Kg/ m	S/S Kg/ m	Min. mm	Max . mm	Mm	P/E Kg/ m	S/S Kg/ m	Min. mm	Max . mm	Mm	P/E Kg/ m	S/S Kg/ m
1/2	15	21.3	21.0	21.4	2.0	0.947	0.956	21.0	21.8	2.6	1.21	1.22	21.0	21.8	3.2	1.44	1.45
3/4	20	26.9	26.4	26.9	2.3	1.38	1.39	26.5	27.3	2.6	1.56	1.57	26.5	27.3	3.2	1.87	1.88
1	25	33.7	33.2	33.8	2.6	1.98	2.00	33.3	34.2	3.2	2.41	2.43	3.3	34.2	4.0	2.93	2.95
1-1/4	32	42.2	41.9	42.5	2.6	2.54	2.57	42.0	42.9	3.2	3.10	3.13	42.0	42.9	4.0	3.79	3.82
1-1/2	40	48.3	47.8	48.4	2.9	3.23	3.27	47.9	48.8	3.2	3.56	3.60	47.9	48.8	4.0	4.37	4.41
2	50	60.3	59.6	60.2	2.9	4.08	4.15	59.7	60.8	3.6	5.03	5.10	59.7	60.8	4.5	6.19	6.26
2-1/2	65	76.1	75.2	76.0	3.2	5.71	5.83	75.3	76.6	3.6	6.42	6.54	75.3	76.6	4.5	7.93	8.05
3	80	88.9	87.9	88.7	3.2	6.72	6.89	88.0	89.5	4.0	8.36	8.53	88.0	89.5	4.8	9.90	10.10
4	100	114.3	113.0	113.9	3.6	9.75	10.00	113.1	115.0	4.5	12.20	12.50	113.1	115.0	5.4	14.50	14.80
5	125	139.7	-	-	4.5	15.00	-	138.5	140.8	4.8	15.90	16.40	138.5	140.8	5.4	17.90	18.40
6	150	165.1	-	-	4.5	17.80	-	163.9	166.5	4.8	18.90	19.50	163.9	166.5	5.4	21.30	21.90
6	150	168.3	-	-	4.5	18.20	-	-	-	4.8	19.40	-	-	-	H1-5.4	21.70	-
6	150	168.3	-	-	-	-	-	-	-	-	-	-	-	-	H2-6.3	25.20	-
7	175	193.7	-	-	4.8	22.40	-	-	-	5.4	25.10	-	-	-	5.9	27.30	-
8	200	219.	-	-	4.8	25.4	-	-	-	5.6	29.5	-	-	-	5.9	31.0	-

		1				0					0					0	